

Stretch Wrapping. Case Handling. Shrink Packaging. Palletizing. Conveying.

S-4000

Wrapping System

Productivity

Providing creative solutions to help customers increase productivity.

NOTE: Not all sections of safety fencing shown.

Built for Demanding Applications

- Wrap tall, lightweight unstable loads.
 - Handles liquid/dry product that can spill and require wash down.
- Meets high throughput requirements.
- Wraps over 100 loads per hour.



S-4000

pallet-grip

- Patented "Lock Your Load to the Pallet" System
- Reduce Load Shifting
- Reduce Product Damage



S-4000

Open Design

Patented 2-leg design uses less floor space than other overhead models. Design transmits stress forces on the frame to the ground.

Load Seeking Clamp

- Exclusive clamp "seeks out" load & holds film against the load
- Eliminates beginning film tails
- Improves containment

Uptime

AC drives and motors ensure maximum uptime in a high speed operation.

NOTE: Standard safety fencing not pictured.

Safety

Interlocked gate shuts the machine down if the gate is opened. A category 3 safety circuit is included.

Safety rated light guards included.

Easy Film Loading

Designed with the operator in mind. No need to stand on the conveyor and there are no pinch points.

Load Handling

Special conveyor staging eliminates wasted time to achieve over 100 loads per hour.

S-4000 Specifications

PERFORMANCE CRITERIA

■ Production Speed based on 80" load height; 2 film layers

■ Maximum Load Size

FILM DELIVERY SYSTEM

■ Power Roller-Stretch® Plus

■ Wrapping Force ■ Pallet-Grip

250% Stretch (Standard) 100-300% available Electronically controlled

147.3 cm L x 147.3 cm W x 203.2 cm H (Requires optional 152.4 cm EW conveyor system)

Standard

100 - 120 loads per hour

PNEUMATIC DATA

■ 3-5 CFM @ 80 psi clean, dry air Standard

MACHINE SHIPPING WEIGHT

■ Shipping Weight (including skid - approximate) 5896.700 kg

ELECTRICAL DATA

■ Voltage■ System Logic■ NEMA 12-enclosure

400V, 32A PLC/Touchscreen and Ethernet

Standard

SERVICE SUPPORT


24 hrs/7 days a week



Lan-Logix**

The Lan-Logix interface leads the industry to boost productivity by eliminating the need for costly software and hardware to make minor program changes. Included are multiple wrap patterns,

precise wrap pattern control, password protection, and extensive efficiency data capture.



Specifications subject to change without notice. Lantech systems and sub-systems are protected by U.S. and foreign patents. Additional U.S. and foreign patents pending. © Lantech.com 2011

MEMBER РММІ USA